

Honda 10000

Specifications

MAXIMUM AC OUTPUT (WATTS)	10000
AC Voltage Available	120/240
MAXIMUM CONTINUOUS AC OUTPUT (WATTS)	9000
Max. Rated AC Amperage @ 120 V/240 V	37.5 x 2 (75.0/37.5)
GROUND FAULT CIRCUIT INTERRUPTER (GFCI)	Standard
FREQUENCY (HERTZ)	60
AUTOMATIC VOLTAGE REGULATOR	Standard DAVR (Digital Automatic Voltage Regulator)
DC Output Volts/Amps	N/A
Engine Type	Honda GX630H OHV, 90° V-Twin design, 4-stroke, air-cooled
DISPLACEMENT	688 cc
STARTING SYSTEM	Electric
Low Level Oil Alert System	Standard
AUTO THROTTLE	Standard
REMOTE START CAPABILITY	No
REMOTE START KIT PART NUMBER INFO	N/A
FUEL TANK CAPACITY (LITRES)	31 litres (6.82 Imp. gal)
TRANSPORT WHEELS	2 Wheel standard
LIFTING HOOK	Standard
BATTERY	Standard
Approximate Running Time/Tankful (hrs)	6.5**
Rated Fuel Consumption (Litres/Hour)	4.77**
Noise Level dB(A) (1.5 m to 7 m)	72**
Length (Without Handles and Wheels)	973 mm (38.3 in.)
Length (With Handles and Wheels)	1,420 mm (55.9 in.)
Width (Without Handles and Wheels)	552 mm (21.7 in.)
Width (With Handles and Wheels)	703 mm (27.7 in.)
Height (Without Lift-Hook)	695 mm (27.4 in.)
Height (With Lift-Hook)	891 mm (35.1 in.) standard
DRY WEIGHT	183.0 kg (403.4 lb) including battery
COLD CLIMATE TECHNOLOGY	Standard