

HONDA 3000

Specifications

GENERATOR TYPE	INVERTER
MAXIMUM AC OUTPUT (WATTS)	3000
VAC VOLTAGE AVAILABLE	120
MAXIMUM CONTINUOUS AC OUTPUT (WATTS)	2800
MAX. RATED AC AMPERAGE @ 120 V / 240 V	23.3 / -
GROUND FAULT CIRCUIT INTERRUPTER (GFCI)	N/A
FREQUENCY (HERTZ)	60
AUTOMATIC VOLTAGE REGULATOR	STD.
DC OUTPUT (VOLTS / AMPS)	12 / 8.3
Honda ENGINE	GX200T2
TYPE	OHV; 4-STROKE; AIR-COOLED
DISPLACEMENT	196 cc
STARTING SYSTEM	ELECTRIC / RECOIL
LOW LEVEL OIL ALERT™ SYSTEM	STD.
AUTO THROTTLE	ECO-THROTTLE™ STD.
REMOTE START CAPABILITY	NO
REMOTE START KIT PART NUMBER INFO	N/A
FUEL TANK CAPACITY (LITRES)	13
TRANSPORT WHEELS	OPT. 4-WHEEL P/N 06423-ZS9-T30/06424-ZS9-000AH
LIFTING HOOK	N/A
BATTERY	STD (P/N 31500-HN1-003AH)
APPROXIMATE RUNNING TIME / TANKFUL (HRS.)	7.2** / 20***
RATED FUEL CONSUMPTION (LITRES / HOUR)	1.78**
NOISE LEVEL dB(A) (1.5 METRES TO 7 METRES)	58** / 48***
LENGTH	655 mm (25.8 IN.)
LENGTH - WITH HANDLES FOLDED	N/A
LENGTH - WITH HANDLES	N/A
WIDTH - WITHOUT HANDLES AND WHEELS	445 mm (17.5 IN.)
WIDTH - WITH WHEELS	N/A
HEIGHT - WITHOUT LIFT-HOOK	555 mm (21.8 IN.)
HEIGHT - WITH LIFT-HOOK	N/A
DRY WEIGHT	59 kg (130 LB.)
LENGTH - WITHOUT HANDLES AND WHEELS	N/A
LENGTH - WITH HANDLES AND WHEELS	N/A
WIDTH - WITH HANDLES AND WHEELS	N/A
COLD CLIMATE TECHNOLOGY	YES

